



Detcon Model DM-700-N2H4

ISO 9001: 2000
Certified

888-367-4286
281-367-4100
fax 281-292-2860
www.detcon.com
sales@detcon.com

Specifications

Sensor Type

Electrochemical Fuel Cell

Measurement Range

0-1 ppm, Other ranges available

Accuracy/Repeatability

±2% FS

Response/Clearing Time

T90 <120 seconds

Span Drift

<5% signal loss per month

Operating Temperature Range

-10°C to +40°C; +14°F to +104°F

Operating Humidity Range

10-95% RH non-condensing

Outputs

Linear 4-20 mA DC
RS-485 MODBUS-RTU

Input Voltage

11.5-28 VDC

Power Consumption

<2 1/2 watts @ 24 VDC

Electrical Classification

Explosion proof
Class I, Division 1, Groups A, B, C, D
Class I, Zone 1, Group IIC (ATEX)

Safety Approvals

cCSAus, ATEX
SIL1 FMEDA Rating

Sensor Life/Warranty

Sensor - 1 year; Transmitter 2 Years

Dimensions

7" High x 2 1/8" Diameter (sensor only)

Hydrazine Sensor

Electrochemical Fuel Cell

(shown as PN 967-262694-001 in SS junction box)



Description

Detcon Model DM-700-N2H4 Hydrazine sensors are non-intrusive "Smart" sensors designed to detect and monitor N2H4 in air over the range of 0-1 ppm. The sensor assembly is constructed of electropolished 316SS and consists of two parts – an encapsulated universal Intelligent Transmitter Module (ITM), and a plug-in electrochemical cell with intelligent sensor interface. The plug-in intelligent sensor automatically identifies itself to the ITM and allows for seamless field interchangeability. Operator interface is via a small handheld magnet. One of the main features is the embedded intuitive software that guides the user through routine calibration and configuration menus using a built-in LED alpha/numeric display. Included is a splash-guard with integral cal port.



www.detcon.com

Features

Failsafe User-Friendly Interface

- ▶ LED Display (With Antiglare Cover)
- ▶ Full Text Display Method
- ▶ Non-intrusive Interface
- ▶ Auto Zero/Auto Span
- ▶ Pre-emptive Fault Diagnostics
- ▶ Scrolling Full Message/Text Display

(Input Voltage Range, Operating Temperature Range, Detector Signal Amplitude, Output Signal Loop Integrity)



Environmentally Bulletproof

- ▶ Electropolished 316SS Construction
- ▶ 100% Epoxy Encapsulated Circuitry
- ▶ Bullet-Proof I/O Protection (Over-voltage, Miswiring, EMI/RFI Immunity)
- ▶ Water-Proof, Corrosion-Proof, Vibration-Proof

Modular and Serviceable

- ▶ Modular Design
- ▶ Plug and Play Components
- ▶ Quick Thread Release (For Sensor Replacement)
- ▶ Integral Calibration Port

Order Guide Specify junction box options (below)

- | Part Number | Description |
|------------------|--|
| ▶ 967-262690-001 | DM-700-N2H4 Sensor Assembly (no junction box) |
| ▶ 967-262691-001 | DM-700-N2H4 Sensor Assembly with Aluminum Junction Box |
| ▶ 967-262694-001 | DM-700-N2H4 Sensor Assembly with 316 SS Junction Box |

Accessory Modules

- ▶ Remote Control/Alarm Relay Module
- ▶ Hart Integration Module
- ▶ Profibus Integration Module
- ▶ Foundation Fieldbus Integration Module
- ▶ Wireless Integration Module