



Model 1000-H2S

Hydrogen Sulfide
Process Analyzer

Toll Free: 888-367-4286

Phone: 713-559-9200

Fax: 281-292-2860

<http://www.detcon.com>

e-mail: sales@detcon.com

Electrochemical Sensor Technology

SPECIFICATIONS

Sensor Type

3-Electrode Electrochemical

Measurement Range

0-1,000 ppm

0-2%

0-5%

Accuracy/Repeatability

±10% of reading

or ±2.5% of range

whichever is greater

Response/Clearing Time

T50 <30 seconds

T90 <1 minute

Max output to over-range gas: <10 seconds

Operating Temperature Range

-40°F to +122°F; -40°C to +50°C

Operating Pressure Requirements

Inlet: 10 ±2 psig

Vent: Atmospheric ±1 psig

Outputs

Linear 4-20 mA DC

RS-485 Modbus™

3 Relays (alarm 1, alarm 2, & fault)

Contacts rated 5 amps

Power Input

117/220 VAC

22-24 VDC

Electrical Classification

Explosion proof

Class 1, Division 1, Groups B, C, D

Sensor Life/Warranty

Sensor: 2 year

Transmitter: 2 year warranty

Analyzer Weight

80 lbs.

Shipping Weight

140 lbs

Dimensions

29" x 29" x 8"

NOTE: Sample conditioning requirements are handled separately.



DESCRIPTION

Detcon High Range Model 1000-H2S Process Analyzer is designed to provide continuous, accurate real-time measurement of hydrogen sulfide gas concentrations in a wide variety of process gas streams. With new technology and design, the High Range Process Analyzer has a measurement range of 0-1,000 ppm with up to 2% standard and up to 5% with additional high range applications packaging. All process analyzers in the Model 1000 Series employ Detcon's 3-Electrode Electrochemical sensor element and features a microprocessor-based signal-conditioning transmitter with local digital display, fault supervision, calibration mode indicator, 4-20mA, alarm relays and an RS-485 serial port. The instrument package is rated (explosion proof) Class1, Division 1, Groups B, C, D.