



Model 1000-H2S

Hydrogen Sulfide
Process Analyzer

Toll Free: 888-367-4286

Phone: 281-367-4100

Fax: 281-292-2860

<http://www.detcon.com>

e-mail: sales@detcon.com

Solid State MOS Sensor Technology

APPLICATIONS

- Natural Gas Pipelines
- Tail Gas Lines
- SRU Overhead Gas Lines

SPECIFICATIONS

Sensor Type

Solid State Metal Oxide Semiconductor

Measurement Range

0-10 ppm up to 0-10,000ppm

Higher ranges available on request

Accuracy/Repeatability

±10% of reading

or ±2.5% of range

whichever is greater

Response/Clearing Time

T50 <90 seconds

T80 <4 minutes

Max output to over-range gas: <10 seconds

Operating Temperature Range

-40°F to +167°F; -40°C to +75°C

Operating Pressure Requirements

Inlet: 10 ±2 psig

Vent: Atmospheric ±1 psig

Outputs

Linear 4-20 mA DC

RS-485 Modbus™

3 Relays (alarm 1, alarm 2, & fault)

Contacts rated 5 amps

Power Input

117/220 VAC

22-24 VDC

Electrical Classification

Explosion proof

Class 1, Division 1, Groups B, C, D

Sensor Life/Warranty

Sensor: 10 year conditional warranty

Transmitter: 2 year warranty

Analyzer Weight

80 lbs.

Shipping Weight

140 lbs

Dimensions

29" x 29" x 8"

NOTE: Sample conditioning requirements are handled separately.



DESCRIPTION

Detcon Model series 1000-H2S process analyzers provide continuous, real-time measurement of H2S concentrations in natural gas pipelines, tail gas lines, SRU overhead gas lines, as well as other applications. Available ranges are from 0-10 ppm up to 0-10,000 ppm (1%). Higher ranges are available on request. The system can be provided with manual calibration or with microprocessor-controlled automatic calibration. Both designs employ Detcon's proprietary solid state MOS sensor element with a ten-year conditional warranty. The analyzer features a microprocessor-based signal-conditioning transmitter with local digital display, fault supervision, calibration mode indicator, alarm relays and an RS-485 serial port. The instrument package is rated for use in electrically classified areas: Class I; Division 1; Groups B, C, and D. Line power, battery and solar powered models are available.